

PARKLIO™ CHAIN

TECHNICAL SPECIFICATIONS



Automatic with remote control on your smartphone

24VDC chain barrier for residential and collective use

Up to 20m width passage barrier

High usage factor

Obstacle detection

Self-learning of open/close distances (encoder)

Electronic soft start-soft stop

Use of external limit switches (encoder)

Housing for battery backup

Downloadable application for your smartphone

A temporary digital key for your visitors

Power supply (Vac/Hz)	230/50
Power consumed (W)	170
Absorbed current (A)	5,5
Motor voltage (Vdc)	24
Opening time (s)	10
Lock	Yes
Limit switches	No
Encoder	Yes
Duty cycle	Intensive use
Protection level	IP54
Operating temperature (°C)	-20/60
Motor weight (kg)	46
Packaging dimensions (cm)	25 X 22 X 108
Chain maximum length (m)	20
Length of the chain (m)	4, 6, 8, 10, 12, 14, 16, 18, 20
Relative height in the middle (cm)	75, 70, 65, 60, 55, 50, 45, 40, 35

INSTRUCTIONS AND SUPPORT:

www.parklio.com/support/

APPLICATION DOWNLOAD:

(Android)

https://play.google.com/store/apps/details?id=com.parklio.parklio746237&hl=en_US

(Apple)

<https://itunes.apple.com/hr/app/parklio/id1316429271?mt=8>

by access Id & Security

-  España
-  Portugal
-  Cabo Verde
-  Guinea Ecuatorial
-  Camerún
-  Marruecos

Los datos técnicos e informaciones que aparecen en este catálogo no tienen valor contractual y pueden ser modificados por los fabricantes de dichos artículos. Todos los nombres propios de programas, sistemas operativos, equipos hardware, etc., que aparecen en este catálogo son propiedad de sus respectivas compañías u organizaciones.



SISTEMAS BYACCESS, S.L.

C/ Puente de Madrid, 28
28412 - Cerceda - Madrid
SPAIN
Tel: +34 918 420 129
info@byaccess.com
www.byaccess.com



**Sistemas
Seguridad.com**



Sistemasseguridad.com

GRUPO SDI
"Associated Partner"

Oficina Central y SAT.

C/ Puente de Madrid, 28
28412 - Cerceda - Madrid
SPAIN
Tel: +34 918 420 130
info@grupo-sdi.com



identialia



www.identialia.com